

DURABIL CUTTER CADDY

ITEMNUMBER	DESCRIPTION	WEIGHT
CC3	Cutter Caddy-Fixed Height-Even Tires-Mowers Up To 10'6"	1500
CC3HL	Cutter Caddy-Hyd Lift-Even Tires-Mowers Up To 10'6"	2500
CC2	Cutter Caddy-Fixed Height-Offset Tires-Mowers Up To 9'6"	1176
CC2HL	Cutter Caddy-Hyd Lift-Offset Tires-Mowers Up To 9'6"	1396
CC3WK	Aux Weight Kit-May Be Needed For Some 10'6" Mowers	
CC2WK	Auxilliary Weight Kit	

Cutter Caddies

- Improved turning capability
- Easy tractor hookup
- Improved flotation for mower
- Easy bolt-on application for disc mowers
- Fixed height and hydraulic lift models
- Accommodates mowers up to 10'6"

*Check whether the mower to be used requires the tractor 3 point hitch to be raised prior to raising the disc mower into transport position. As of this time the following mowers require a hydraulic lift cutter caddy: Kuhn (including any OEM machines produced by Kuhn-JD,Gehl). **Vicon** mowers do not require a hydraulic lift Cutter Caddy.



Even wheel design, as opposed to offset wheels, provides more stability and eliminates tire dragging on turns.

With more weight placed ahead of the mower the caddy can be unhitched from the tractor with the mower in transport position. Mowers up to 10'6" can be used. Offset wheel models also available:



Width: 84"
Length: 13'



Woodward Crossings, Inc.
www.WoodwardCrossings.com
814-349-4484

DURABILIT TUMBLEBUG

ITEMNUMBER	DESCRIPTION
TB1810	Tumblebug Single Bale Transporter - Add Wheels And Tires
TBTIRE	Set Of Two Mud & Snow Tires For Tumblebug - 15" Rims
TB1850UR	Tumblebug Unroller Kit
TBWIRE	Tumblebug Extra Tow Vehicle Wiring Kit

TUMBLEBUG

- No winches, ropes, or hydraulics
- Works with a truck or tractor
- 2" ball coupler
- 12V electric brakes
- Wiring kit for towing vehicle

OA length: 144"
Width between wheels: 82"



1 Back up to a bale, engage brake switch



2 Continue backing until loading arm falls over frame of cradle and touches hay



3 Pull forward slowly and the bale rolls on the cradle



4 Disengage switch (release brakes) and go



Woodward Crossings, Inc.
www.WoodwardCrossings.com
814-349-4484

DURABILT LANDSCRAPERS

ITEMNUMBER	DESCRIPTION	WEIGHT
LS06	Landscaper-6'-Complete W/Tires,Cylinder,Hoses & Jack	1082
LS08	Landscaper-8'-Complete W/ Tires,Cylinder,Hoses & Jack	1260
LS10	Landscaper-10'-Complete W/Tires,Cylinder,Hoses & Jack	1500
LS12	Landscaper-12'-Complete W/Tires,Cylinder,Hoses & Jack	1740
LS14	Landscaper-14'-Complete W/Tires,Cylinder,Hoses & Jack	1980
LS12HD	Landscaper-12' Heavy Duty- Complete W/Tires,Cylinders,Hoses & Jack	2040
LS14HD	Landscaper-14' Heavy Duty- Complete W/Tires, Cylinders,Hoses & Jack	2230

LANDSCRAPER

- Grade roads and driveways
- Landscape lawn & farm yard
- 1/2" x 6" cutting edge, 20" Moldboard Height
- Complete with tires, jack, cylinder & hoses

MODEL	WIDTH	Min. HP.	LENGTH	TIRES	TONGUE	WEIGHT
LS-06 (Fixed Tongue)	6'	40	12'6"	7.60/15	4"x4"	1082#
LS-08 (Fixed Tongue)	8'	40	12'6"		WELDED	1260#
LS-10 (Swivel Tongue)	10'	50	14'6"	11L/15	4" x6" BOLTED (SWIVEL)	1500#
LS-12 (Swivel Tongue)	12'	60	14'6"			1740#
LS-14 (Swivel Tongue)	14'	80	14'6"			1980#
LSHD12 Heavy Duty	12'	80	14'6"			2040#
LSHD14 Heavy Duty	14'	80	14'6"	2 pair 11L/15		2230#
TS08/CTS08 Tilting	8'	40	12'6"	7:60/15		1354#
TS10/CTS10 Tilting	10'	50	14'6"	11L/15		1532#
CTS12 Tilting	12'	60	14'6"	11L/15		1710#



Tilt Landscrapers



CTS Models with Center Tilt Axle.

TILT LANDSCRAPERS

ITEMNUMBER	DESCRIPTION	WEIGHT
TS08	Landscaper-8'-W/Tilt-Complete W/Tires,Cylinders,Hoses & Jack	1354
CTS08	Landscaper-8'W/Center Tilt Axle-Complete W/Tires, Cylinders, Hoses & Jack	1354
TS10	Landscaper-10'-W/Tilt-Complete W/Tires,Cylinders,Hoses & Jack	1532
CTS10	Landscaper-10'W/Center Tilt Axle-Complete W/Tires, Cylinders, Hoses & Jack	1532
TS12	Landscaper-12'-W/Tilt-Complete W/Tires, Cylinders, Hoses & Jack	1740
CTS12	Landscaper-12'W/Center Tilt Axle-Complete W/Tires, Cylinders, Hoses & Jack	1740
TSLI	Level Indicator	



Woodward Crossings, Inc.
www.WoodwardCrossings.com
814-349-4484

DURABILT DIRT PAN

ITEMNUMBER	DESCRIPTION	WEIGHT
DP60	Dirt Pan-60"-1.5 Yard-Complete W/Tires,Cylinders,Hoses & Jack	1500
DP84	Dirt Pan-84"-3 Yard-Complete W/Tires,Cylinders,Hoses & Jack	1630
DP84HC	Dirt Pan-84"-4 Yard-Complete W/Tires,Cylinders, Hoses And Jack	2000
DP84HCD	Dirt Pan 84"-4 Yard-Same As DP84HC Except With Clevis Hitch And Lift Axle	2160

Dirt Pan

Provides an efficient means of scooping, lifting, and moving soil between points without dragging the soil.

- Attaches to bottom links of 3pt hitch (DP84HCDB uses a clevis hitch)
- Cutting depth controlled by 3pt hitch (DP84HCDB by lift axle)
- Dig angle and dump height controlled by cylinders-single remote required (double for DP84HCDB)

Complete w/tires, cylinders & hoses

	DP60	DP84	DP84HC	DP84HCDB
Pan Capacity	1.5 yard (Heaped)	3 yards (heaped)	4 yards (heaped)	4 yards (heaped)
Cutting Width	60"	84"	84"	84"
Cutting Depth	0-3"			
Dump Height	0-8"			
Tires	7.60 x15	11Lx 15	Dual 11Lx15	Dual 11Lx15
Weight	1500#	1630#	2000#	2160#
Horsepower Required	30-60 HP	60-100 HP	80-120 HP	80-120 HP
Cylinders	(2) 3" x 8"		(4) 3" x 8"	



DP84HCDB with dual tires, double cylinders



DP84HCDB with dual tires, drawbar, lift axle, and clevis hitch



Woodward Crossings, Inc.
www.WoodwardCrossings.com
814-349-4484

DURABILT UTILITY GRADER

ITEMNUMBER	DESCRIPTION	WEIGHT
GR08	Grader Blade-8'-Complete W/Tires,Cylinder & Hoses	1150

Utility Grader

IDEAL FOR:

- Driveways
- Terracing
- Leveling
- Width: 96"
- Manual Angle: Approx. 45 degrees
- Tilt: Approx. 20 degrees
- Bottom link hookup
- Complete w/tires, cylinder and hoses
- Single remote required
- Minimum 20 HP- Max 60 HP



SWIVEL SCRAPER

ITEMNUMBER	DESCRIPTION	WEIGHT
SS07	Rear Blade W/Manual Angle Tilt And Offset - Heavy Duty	480
SS08	Rear Blade W/Manual Angle Tilt And Offset - Heavy Duty	530
SSHOK	Hydraulic Offset Kit For Swivel Scrapers	

Swivel Scraper

The Swivel Scraper is a heavy duty rear blade that can be tilted up to 24" from level. It can also be offset from the tractor seat up to 24" right or left with the optional swing cylinder.

FEATURES:

- Category 1 or 2, 3pt hitch
- Swivel 360 degrees
- 1/2" x 6" Reversible Cutting Edge
- Optional Swing Cylinder



MODEL	Overall Width	HP Requirement	Shipping Weight
SS07	7'	25 HP	480 lbs.
SS08	8'	35 HP	530 lbs.



Woodward Crossings, Inc.
www.WoodwardCrossings.com
 814-349-4484

DURABILT PASTURE PUNCH AERATOR

ITEMNUMBER	DESCRIPTION	WEIGHT
PP063PT	Pasture Punch-6' - 3 Pt Lift/ Weld On Spikes. Filled Weight 3100#	1800
PP08	Pasture Punch-8'-W/Tires, Cylinder & Hoses. Filled Weight 4250#	2450
PP08SR	8' Pasture Punch Plus 44" Diameter Smooth Roller Drum	
PP10	Pasture Punch-10'-W/Tires, Cylinder & Hoses. Filled Weight 5045#	2745
PP10SR	10' Pasture Punch Plus 44" Diameter Smooth Roller Drum	
PP12	Pasture Punch-12'-W/Tires, Cylinder & Hoses. Filled Weight 5965#	3143
PP12SR	12' Pasture Punch Plus 44" Diameter Smooth Roller Drum	

Pasture Punch

- Used by:
- Sod Farmers
 - Hay – Pastures
 - Alfalfa Growers
 - Landscapers
 - Sports Complexes
 - Relieves Compaction
 - Promotes Air & Water Movement
 - Increases Decomposition of Dead Plant Matter
 - Relieve Root Bound Plants
 - Help Activate Fertilizer

Model	Drum Width	Empty Weight	Filled Weight	Min. Hp.	Number of Tines
PP06- 3 Point	64"	1800#	3100#	45	55
PP08 (Single Wheels)	88"	2450#	4250#	45	75
PP10 (Single Wheels)	112"	2745#	5045#	60	100
PP12 (Standard w/Dual Wheels)	136"	3143#	5965#	80	125

PP-SR Models include an interchangeable 44" smooth roller drum.

Tines are 3/4" thick, 7" long, and 4" wide at the base. Tines are hard surfaced. Drum diameter: 30"



Smooth Rollers(SR Models) are the same as Pasture Punch, less tines.

SMOOTH ROLLERS

ITEMNUMBER	DESCRIPTION	WEIGHT
SR08	Roller-8'-W/Tires,Cylinder & Hoses. Filled Weight: 5450#	2450
SR08NA	Roller-8' Smooth-Less Lifting Axle	2200
SR10	Roller-10'-W/Tires,Cylinder & Hoses. Filled Weight: 6600#	2745
SR10NA	Roller-10' Smooth-Less Lifting Axle	2495
SR12	Roller-12'-W/Tires,Cylinder & Hoses. Filled Weight: 7850#	3143
SR12HD	Roller Heavy Duty-12'-W/Tires, Cylinder & Hoses	3600
SR14HD	Roller Heavy Duty-14'-W/Tires, Cylinder & Hoses	3850



Woodward Crossings, Inc.
www.WoodwardCrossings.com
814-349-4484